Remplacement du cadre de porte en fonte autoportant Riva2

IMPORTANT : Assurez-vous toujours que le poêle est complètement froid avant de le toucher, de le nettoyer ou d'effectuer toute opération d'entretien. **N'essayez aucune intervention tant que l'appareil n'a pas entièrement refroidi afin d'éviter tout risque de brûlure ou de blessure.**

1. Retirez la porte en la soulevant délicatement hors des axes de charnière.

2. Dévissez les 2 vis pour retirer la porte du cendrier.

3. Localisez les quatre écrous hexagonaux.

4. Desserrez les 4 écrous hexagonaux à l'aide de l'outil fourni.

5. Soulevez délicatement le cadre vers le haut et éloignez-le du poêle.

6. Retirez complètement les quatre écrous hexagonaux et installez-les sur le nouveau cadre. Lors du resserrage, veillez à ne pas exercer un couple excessif ni à trop serrer.

PR3416 • Numéro 1
Juin 2026

Replacing Riva2 Freestanding Cast Iron Door Frame

IMPORTANT: Always ensure the stove is completely cold before touching, cleaning, or carrying out any maintenance. **Do not attempt any work until the appliance has fully cooled to avoid the risk of burns or injury.**

1 Remove door by carefully lifting off hinge pins

2 Unscrew 2 x screws to remove ashpan door

3 Locate four hex nuts

4 Loosen 4 hex nuts using tool provided

5 Carefully lift frame up and away from stove

6 Fully remove four hex nuts and fit into new frame. When tightening back up be careful not to over-torque or overtighten.

PR3416 • Issue 1
June 2026